

1125 Litre 3000 PSI Pressure Washer EU Highway Bowser



****Bowser may vary slightly to the model pictured, however they will still perform the duty detailed****

to be used with a towing pin

Chasis	Constructed from 80 x 80 R.S.A fully welded with a 'T' frame drawbar, all fully hot dipped galvanised. 5mm sheet front mounting plate		
Axles/Suspension	Avonride rubber torsion axle fitted with 200 x 50 auto reverse brakes. 4 stud 5½" pcd hubs		
Wheels/Tyres	2 no. 175 x 13 8 ply commercial van tyres		
Coupling	Knott-Avonride auto reverse coupling fitted with 40km towing eye, break away cable and parking break lever		
Tank	Polyethylene moulded tank elliptical in section, baffled & fitted with an 18" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps. 1 rear tap fitted, 2" bottom drain underneath rear of tank. 2 rear outlets.		
Pump	Yanmar electric start L100 10HP engine driving a 200 Bar (3000 psi), 15Lpm piston pump c/w hand lance & 7m of hose stowed on bracket. Fuel consumption approx. 1.5 L/Hr, running time approx 2.9 hours		
Ancillary Equipment	Moulded mudguards, mud flaps, front telescopic jockey wheel, side reflectors, rear lighting board c/w 13 pin plug		
Finish	Tank moulded in yellow, blue or green polyethylene. Chassis galvanised		
Optional Extra	15mm high pressure hose on hose reel, quotation available upon request		
Dimensions (Approx.)	Width 1.55m (61")	Laden Max:	1500kg
	Length 3.454m (136")	Unladen Weight:	385kg
	Height 1.346m (53")	Towing Height: (Level)	400mm

EU approved model from October 2012

Nationwide Service Telephone 0800 731 0589

www.tardishire.co.uk