

Dimensions: 3454mm Long x 1550mm Wide x 1346mm High

Please use E5 fuel only

“to be used with towing pin”



**During freezing conditions the pump must be drained to avoid damage

Please ensure pressure washers are not kept outside and exposed to the elements during the cold winter weather as this will cause damage

CHASSIS: Constructed from 100 x 50 RSC fully welded, with front standing plate and an 'A' frame drawbar, 80x80x6 RSA frame, hot dipped galvanised.

AXLE/SUSPENSION: Single 45mm solid square beam axle fitted with heavy duty taper rolled bearing hub.

WHEELS AND TYRES: 2 No. 175 x 13 x 8ply tyres on 4 stud 5.1/2" pcd rims.

COUPLING: 2" solid forged ring eye.

TANK: Polyethylene, elliptical in section with internal anti surge baffle, 3/4" front draw off, 2 rear outlet connections, fitted with a 22" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps.

PUMP:

Pressure: (PSI/Bar) 3000 / 200

Engine Type: Honda GX390 Petrol

Water Flow: 15 litres per minute

Weight: 85kg

Dimensions: (H x W x L) 800 x 650 x 850mm

Drive Type: Gearbox 2:1 reduction

ANCILLARY EQUIPMENT: T27 Adjustable Screw Leg.

- Unladen Weight: 370kg
- Laden Max: 1460kg
- Towing Height: (Level) 460mm

Bowers may vary slightly to the model pictured, however they will still perform the duty detailed