

Dimensions: 3.555m Long x 1.550m Wide x 1.524m High



CHASSIS: Constructed from 100 x 50 RSC fully welded with front standing plate and 'A' frame drawbar

AXLE/SUSPENSION: Single Avonride torsion beam axle and fitted with 200 x 50 Auto reverse brakes on 4 stud 5 ½" pcd hubs

WHEELS AND TYRES: 2 No 175 x 13 x 8 ply radial tyres fitted to 4 stud 5 ½" pcd rims.

COUPLING: Knott 2000kg posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable & 40mm ring eye or 50mm ball.

ANCILLARY EQUIPMENT: Moulded mudguards, rear support stand, telescopic front jockey wheel, full road lighting c/w 7 pin plug.

OUTER BUND TANK: Cylindrical in section with removable top section for tank access. Rear access

door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank. 4 lifting eyes & fork truck sockets.

INNER FUEL TANK: Constructed from translucent heavy duty polyethylene with a capacity of 980 Litres. 2" filler with cap & chain. 1" vent valve, ½" top mounted suction & return connections. P.R.V. in tank top. Bottom outlet valve.

PUMP: K1 semi rotary hand pump c/w in line 'Y' strainer 15' of hose & trigger nozzle.

Technical Specifications

- Laden weight: 1500kg
- Unladen Weight 476kg
- Towing height (level) : 560mm

TO BE USED WITH TOWING PIN