

Dimensions: 3.555m Long x 1.550m Wide x 1.524m High

TO BE USED WITH TOWING PIN



CHASSIS: Constructed from 100 x 50 RSC fully welded with front standing plate and 'A' frame drawbar.

AXLE/SUSPENSION: Single Avonride torsion beam axle and fitted with 200 x 50 Auto reverse brakes on 4 stud 5 ½" pcd hubs

WHEELS AND TYRES: 2 No 175 x 13 x 8 ply radial tyres fitted to 4 stud 5 ½" pcd rims.

COUPLING: Knott 2000kg posibrake over run auto reverse c/w spring assisted handbrake lever, breakaway cable & 40mm ring eye or 50mm ball.

ANCILLARY EQUIPMENT: Moulded mudguards, rear support stand, telescopic front jockey wheel, full road lighting c/w 7 pin plug.

OUTER BUND TANK: Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank. 4

lifting eyes. Fork truck sockets for use when tank not fitted in chassis.

INNER FUEL TANK: Constructed from translucent heavy duty polyethylene with a capacity of 980 Litres. 2" filler with cap & chain. 1" vent valve, ½" top mounted suction & return connections. P.R.V. in tank top. Bottom outlet valve.

PUMP: 12 volt flameproof. 110Ah battery in box, Racor filter monitor, 7M hose stowed on Bracket, bonding reel, ZVF trigger nozzle. Sample hand pump. Non re-sale flowmeter.

OPTIONAL EXTRAS: 15 Amp solar charge. Fire Extinguisher

Technical Specifications

- Laden weight: 1500kg
- Unladen Weight 476kg
- Towing height (level) : 560mm