

**TARDIS**

ENVIRONMENTAL UK

1125 Litre 3000 PSI Pressure Washer EU Highway Bowser

| | | | |
|-----------------------------|--|------------------------|--------|
| Chasis | Constructed from 80 x 80 R.S.A fully welded with a 'T' frame drawbar, all fully hot dipped galvanised. 5mm sheet front mounting plate | | |
| Axles/Suspension | Avonride rubber torsion axle fitted with 200 x 50 auto reverse brakes. 4 stud 5½" pcd hubs | | |
| Wheels/Tyres | 2 no. 175 x 13 8 ply commercial van tyres | | |
| Coupling | Knott-Avonride auto reverse coupling fitted with 40km eye or 50mm ball, break away cable and parking break lever | | |
| Tank | Polyethylene moulded tank elliptical in section, baffled & fitted with an 18" lockable outer hinged manlid cover, inner sealed vented manlid. Tank secured to chassis with 2 stainless steel straps. 1 rear tap fitted, 2" bottom drain underneath rear of tank. 2 rear outlets. | | |
| Pump | Yanmar electric start L100 10HP engine driving a 200 Bar (3000 psi), 15Lpm piston pump c/w hand lance & 7m of hose stowed on bracket. Fuel consumption approx. 1.5 L/Hr, running time approx 2.9 hours | | |
| Ancillary Equipment | Moulded mudguards, mud flaps, front telescopic jockey wheel, side reflectors, rear lighting board c/w 13 pin plug | | |
| Finish | Tank moulded in yellow, blue or green polyethylene. Chassis galvanised | | |
| Optional Extra | 15mm high pressure hose on hose reel, quotation available upon request | | |
| Dimensions (Approx.) | Width 1.55m (61") | Laden Max: | 1500kg |
| | Length 3.454m (136") | Unladen Weight: | 385kg |
| | Height 1.346m (53") | Towing Height: (Level) | 400mm |

EU approved model from October 2012

Nationwide Service Telephone 0800 731 0589

www.tardishire.co.uk