

**Dimensions: 3.530m Long x 1.498m Wide x 1.524m High**



**CHASSIS:** Constructed from 4" x 2" RSC fully welded with front standing plate and 'A' frame drawbar.

**AXLE/SUSPENSION:** Single Avonride torsion beam axle and fitted with 200 x 50 Auto reverse brakes on 4 stud 5 1/2" pcd hubs.

**WHEELS AND TYRES:** 2 No 185 x 13 x 8 ply radial tyres fitted to 4 stud 5 1/2" pcd rims.

**COUPLING:** Knott 2000kg capacity posibrake over run auto reverse coupling c/w Spring assisted handbrake lever, breakaway cable. Fitted with 40mm ring eye or 50mm ball.

**ANCILLARY EQUIPMENT:** Moulded mudguards, rear support stand, telescopic front jockey wheel, full road lighting c/w 7 pin plug.

**OUTER BUND TANK:** Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of inner tank.

**INNER FUEL TANK:** Constructed from 304 stainless steel with a capacity of 1000 Litres. 2" filler with cap & chain. 1" vent valve, 1/2". P.R.V set at 2psi in tank top. Bottom outlet valve with secondary in line.

**PUMP:** Patay 1" Hand Pump, Racor/Facet, filter monitor. Bonding Reel 7m Hose stowed on bracket, ZVF Trigger Nozzle. Sample Hand Pump

#### **Technical Specifications**

- Laden weight: 1500kg
- Unladen Weight 456kg
- Towing height: 600mm

**DHB – APRIL 2018**

**Tel: 0800 731 0589**  
**www.tardishire.co.uk**

