

Dimensions: 3.684m Long x 1.981m Wide x 1.981m High



CHASSIS: Constructed from 100 x 50 RSC fully welded with front standing plate and 'A' frame drawbar.

AXLE/SUSPENSION: Avonride 3000kg rubber torsion beam fitted with Knott 300 x 60 auto reverse brakes operated via cables and rod.

WHEELS AND TYRES: 2 No 235/85 x 16 x 12 ply radials fitted to 5 stud rims

COUPLING: Knott 3000kg posibrake over run auto reverse c/w. Spring assisted handbrake lever, breakaway cable, 40mm ring eye.

ANCILLARY EQUIPMENT: Rolled steel mudguards, rear support stand, telescopic front jockey wheel, full road lighting c/w 7 pin plug.

OUTER BUND TANK: Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of tank inner tank content. 4 lifting eyes. Fork sockets for use when tank not fitted in chassis.

INNER FUEL TANK: Constructed from translucent heavy duty Polyethylene 2" filler cap and chain. 2" vent valve, top mounted ½" BSP suction and return connections. Ball valve in base of tank to pump with secondary in line. P.R.V. in tank top

PUMP: K2 semi rotary hand pump fitted with 15' of 1" hose C/w trigger nozzle and stowed on bracket. In line 'Y' strainer. All contained within lockable bund area.

Technical Specifications

- Laden Max: 2800kg
- Unladen Weight 850kg
- Towing Height (level): 590mm

DHB – APRIL 2018



Tel: 0800 731 0589
www.tardishire.co.uk

