

Dimensions: 3.582m Long x 1.790m Wide x 1.930m High



CHASSIS: Constructed from 100 x 50 RSC, with 5mm pressed channel section, fully welded with 'A' frame drawbar & front standing plate, pressed rear lighting channel

RUNNING GEAR: Avonride twin 1500Kg torsion beams fitted with 200 x 50 Auto Reverse brakes, Gas strut assisted parking brake, break away cable, Knott 3000 Kg Auto reverse coupling fitted with 40 mm eye or 50 mm ball. 4 No 185 x 13 x 8 ply radial tyres on 4 stud 5 1/2" pcd rims, Tandem mudguards, Telescopic front jockey wheel. Full road lighting c/w 7 pin plug.

OUTER BUND TANK: Cylindrical in section with removable top section for tank access. Rear hinged access door fitted with stainless steel hinge. Bund contains 110% of tank content

INNER FUEL TANK: Constructed from translucent heavy duty polyethylene, baffled, 2" filler cap & chain. 2" vent valve, P.R.V.in tank top, 1/2" bsp suction & return in tank top, Ball valve in base of tank to pump .K2 semi rotary pump c/w 15ft of 1" diesel hose & trigger nozzle stowed on bracket. In line 'Y' strainer. All contained within lockable bund area.

Technical Specifications

- Gross weight: 3000kg
- Unladen Weight 900kg
- Towing Height (level): 394mm
- Variations in towing height +25mm to -45mm

DSB – APRIL 2018



Tel: 0800 731 0589
www.tardishire.co.uk

