

Dimensions: 3.684m Long x 1.981m Wide x 1.981m High



**CHASSIS:** Constructed from 100 x 50 RSC fully welded with front standing plate and 'A' frame drawbar.

**AXLE/SUSPENSION:** Avonride 3000kg rubber torsion beam fitted with Knott 300 x 60 auto reverse brakes operated via cables and rod.

**WHEELS AND TYRES:** 2 No 235/85 x 16 x 12 ply radials fitted to 5 stud rims

**COUPLING:** Knott 3000kg posibrake over run auto reverse c/w. Spring assisted handbrake lever, breakaway cable, 40mm ring eye.

**ANCILLARY EQUIPMENT:** Rolled steel mudguards, rear support stand, telescopic front jockey wheel, full road lighting c/w 7 pin plug.

**OUTER BUND TANK:** Cylindrical in section with removable top section for tank access. Rear access door, fitted with stainless steel hinge and fully lockable. Bund contains 110% of tank inner tank content. 4 lifting eyes. Fork Truck sockets for use when tank not fitted in chassis.

**INNER FUEL TANK:** Constructed from translucent heavy duty Polyethylene 2" filler cap and chain. 2" vent valve, top mounted ½" BSP suction and return connections. Ball valve in base of tank to pump with secondary in line. P.R.V. in tank top

**PUMP:** 12 volt H/Duty pump c/w 110Ah battery, 7m of 1" hose c/w ZVF trigger nozzle and stowed on brackets. Facet filter monitor c/w sample valve. All contained within lockable Bund, earth bonding reel, sample pump to base of tank. Non re-sale flowmeter.

#### Technical Specifications

- Laden Max: 2800kg
- Unladen Weight 850kg
- Towing Height (level): 590mm

DHB – APRIL 2018

Tel: 0800 731 0589  
www.tardishire.co.uk

