

26 TONNE R/W STEER H2O TANKER 16000 LITRE CAPACITY

Dimensions: 9.15 mtrs long x 2.9 mtrs wide x 3.43 mtrs high



2" Female Bauer connectors as standard - 50mm snaplock – these are all WRAS approved stainless steel items

ACCESS: Please review the vehicle dimensions and consider possible restrictions for width, height etc when accessing your site. Advise us if you believe you might have a problem to enable us to offer an alternative vehicle

PUMP SPECIFICATION:

Max flow: 160 m³/h
 Max working pressure: 16 bar
 Max working temp: -10 to +120C
 1,050 litres per minute
 Max working pressure is 7-12 bar

Main Features



This is an ideal tanker where accessibility may present a problem for larger vehicles. The rear wheel steering improved manoeuvrability.

This vehicle can also be prepared to deliver quality assured drinking water

We advise that unless strict testing is carried out to DWI recommendations, that water is boiled before drinking.

All water supplied by us is drawn from authorised water authority sources.

ON BOARD:

- 60 mtrs water delivery hose (more available on request)
- Chapter 8 specification
- Safety equipment to Crossrail specification (details on separate data sheet)
- FORS Bronze standard equipment
- Rear loading and delivery



We can supply most configurations of valve and hose fittings. Please specify when calling



This vehicle is Crossrail compliant. Refer to the relevant data sheet for details

16KRWS – JAN 2017



Tel: 0800 731 0589
www.tardish20.co.uk

